

NEW RESIDENTIAL APPLICATION AND PROCESS INFORMATION PACKET





General Addressing Information

For Addresses in the City of San Antonio

- The City of San Antonio assigns addresses within city limits. A service address must be assigned prior to the installation of an electric or gas service. An Address Verification Letter may be required if service address is not verifiable. This letter is supplied by the City of San Antonio.
- For an assignment of a new address or for an Address Verification Letter, you can submit the form by clicking on the following link: https://docsonline.sanantonio.gov/FileUploads/dsd/RequestforAddress.pdf and submitting to the City of San Antonio's Development Services Addressing Team, either in person at 1901 South Alamo or via email at dstaddressing@sanantonio.gov. For further information, please contact their Land Entitlements Addressing Team at (210) 207-1111.

Outside of City Limits in Bexar County

- CPS Energy assigns addresses outside of City Limits, in Bexar County
 - **Important:** If the address is outside of city limits one of the following documents are required to assign your address:
 - Property survey **OR** Plat with legal description
 - EXTRATERRITORIAL JURISDICTION (ETJ) APPROVAL/ CERTIFICATE OF DETERMINATION: If you are outside San Antonio city limits, you may still be within San Antonio's ETJ. It is suggested that you contact the Development Services Department of the City of San Antonio prior to obtaining any other releases for electrical service. Please contact the City of San Antonio at the Business and Development Services building, 1901 S. Alamo St., (210)-207-1111.

Incorporated Cities That Assign Their Own Addresses

Important: For addresses in an incorporated city, an address verification letter may be required if service address is not found in our system. This letter is supplied by the incorporated city. See list of incorporated cities and contact information.

CITY	EMAIL/WEBSITE	PHONE #	ADDRESS
Alamo Heights	nshealey@alamoheightstx.gov	210-826-0516	6116 Broadway San
			Antonio TX 78209
Balcones	bhtx.gov/departments/city-secretary	210-735-9148	3300 Hillcrest Dr.
Heights			Balcones Heights, TX 78201
Castle Hills	cs@castlehills-tx.gov	210-293-9675	209 Lemonwood
			Castle Hills, TX 78213
Hill Country	www.hcv.org	210-494-3671	116 Aspen Ln
Village			San Antonio, TX 78232
Hollywood Park	jalamia@hollywoodpark-tx.gov	210-494-2023	2 Mecca Dr.
			Hollywood Park, TX 78232
Leon Valley	s.pass@leonvalleytexas.gov	210-684-1391	6400 El Verde Rd.
			Leon Valley, TX 78238
Olmos Park	citysecretary@olmospark.org	210-824-3281	120 W El Prado
			San Antonio, TX 78212
Terrell Hills	www.terrell-hills.com/contact-us	210-824-7401	5100 N New Braunfels Ave
			San Antonio, TX 78209
Windcrest	rdominguez@windcrest-tx.gov	210-655-0022	8601 Midcrown
			Windcrest, TX 78239
Live Oak	dgoza@liveoaktx.net	210-653-9140	8001 Shin Oak Dr.
			Live Oak, TX 78233
Schertz	customercare@schertz.com	210-619-1750	1400 Schertz Pkwy
			Schertz, TX 78154
Universal City	ACM@UCTX.Gov	210-659-0333	2150 Universal City Blvd
(Commercial)			Universal City, TX 78148
Atascosa	911arap@atascosacounty.texas.gov	830-769-2748	711 Broadway
County			Jourdanton, TX 78026
Medina County	medinacoordinator@gmail.com	830-741-8997	1613 Ave K Ste. 101
	_		Hondo, TX 78861



CPS Energy Addressing Requirements for Meter Installation

CPS Energy crews make every effort to assure your meter installation is completed accurately and ready for you when you need it.

To assure there are no delays when submitting your request for a meter installation, please follow the addressing requirements below:

Temporary Meter Loops

• Brace of Temporary tripod - Full Address to include the #T at the end of the address should be stenciled in black paint on the brace of the temporary tripod

Or

• Breaker panel – house number with #T stenciled in black paint

Residential & Commercial Permanent Structure – Single Meter

- Residential Structure has permanent address and Meter Loop is on structure no additional addressing requirement is needed
- No Address on Residential Structure Can have address on a sign in front window (Residential Only) or on Meter Can or Disconnect Panel with full address stenciled in black paint
- Residential Meter Pole Full address should be stenciled in black paint on meter can or disconnect panel
- Commercial Structure with or without a Permanent Address and Meter Loop on Structure Full address should be stenciled in black paint on meter can or disconnect panel

Residential & Commercial Permanent Structure – Multi-Meters (example Duplex)

- Structure has permanent address and Meter Loop is on structure Each Meter Can or Disconnect Panel will need to be labeled with Suite/Apt number only stenciled with black paint. Full address should be on Main Disconnect or Meter Trough.
- No Address on Structure Each Meter Can or Disconnect Panel or Trough should have full address stenciled in black paint to include Suite/Apt. number for that can/panel
- Residential or Commercial Structures with a Meter Rack Full address should be on trough lidor disconnect stenciled in black ink



FIGURE 1600.1 TEMPORARY METER INSTALLATION, URD SERVICE AREA



t Standard installation for URD transformer and placement of TML is on front of lot but may be on rear of lot.

- 2. Padmount transformers will normally be located straddling side property lines however CPS Energy may position transformer at other locations as deemed necessary.
- 3. Customer shall construct the temporary service installation as shown above and maintain it in a safe condition throughout its period of use. CPS Energy reserves the right to disconnect damaged or unsafe TMLs.
- 4. The temporary service installation must be identified with a proper service address before CPS Energy will energize it and install a meter.
- 5. All temporary metering installations will require that the customer obtain utility locates from Texas One Call to prevent damage to primary or secondary cables and/or gas lines and to help avoid possible personal injury.
- 6. Copper grounding electrode conductor (furnished and installed by customer size and installation in accordance with NEC) Refer to section 1700.
- 7. CPS Energy may supply TMLs from a secondary enclosure installed after transformer where deemed necessary and such installation shall not have TML placed closer than 3 ft from secondary enclosure.
- 8. Street number with #T should be stenciled in black paint on disconnect panel or full address with #T at the end should be marked on braces facing street.
- 9. Make sure tripod is secure and not blocking a power source.

Temporary Meter Installation- Overhead



Customer Provides Trenching & Conduit (Residential Electric Only) **START** Call for locates before digging (811 or The service conduit must be The end of the service stub is located 1 to 800-344-8377) FYI- No other gas utility is installed from the existing stub to 2 ft outside of the electric easement. allowed in the trench with CPS Energy the meter location. (Plastic pipe markers are installed to electric service. identify the stub location). CPS Energy's standard service Trench & conduit must be Trench Dig with caution, there may be a gas service conduit is 3". If the existing service installed within limits of the stub above the electric stub. After the width needs stub is a 21/2", the service conduit will same lot or property. inspection, the customer is required to to be min of be $2\frac{1}{2}$ " and a $2\frac{1}{2} \times 3$ " reducer will 5" to 6" cover & compact the gas stub with 6" be installed at the 3"elbow of the quality backfill to protect the integrity of the wide. service raceway. (2½ x 3 " reducer gas pipe. can be purchased at TechLine Inc 210-359-8324). Trench depth needs to be min of 30 " deep.(Equipment may be needed to trench 4" of sand or quality Schedule 40 PVC conduit is 3" schedule 40 PVC long radius 36" for transition of stub) The electric backfill material (NO required for the electric elbow at the service raceway shall conduit must transition from the stub ROCKS) over conduit. service. have a min radius of 24". The without any bends or elbows & be a min of elbows at any pole location shall 24" deep to final grade. be schedule 80 PVC. Notify CPS Energy that Customer is required to backfill the your site is ready for an service trench. Quality backfill is inspection to be required around the pipe to П performed & approved protect the integrity of the pipe. before any backfilling.

Customer will retain ownership of the conduit system until CPS Energy installs & energizes with electric service.

CPS ENERGY

CPS ENERGY Customer Provides Trenching & Conduit (Residential Gas & Electric)

